

Network Interface Modules

Network Interface Modules allow a VersaMax PLC to operate as a master or slave on a network. Modules currently available support DeviceNet master or slave communications and PROFIBUS-DP slave communications. An AS-i master communications is also available.

	IC200BEM002	IC200BEM003	IC200CHS006
Product Name	PLC Network Communications PROFIBUS-DP (Slave). Requires IC200CHS006 Communications Carrier.	PLC Network Communications PROFIBUS-DP (Master). Requires IC200CHS006 Communications Carrier.	VersaMax I/O, Local Communications Carrier (Supports IC200BEMxxx Modules)
Lifecycle Status	Active	Active	Active
Number of Stations	32 without repeaters; up to 125 with repeaters	125 PROFIBUS DP Slave devices	N/A
I/O Data	384 Bytes maximum; up to 244 bytes of inputs or 244 bytes of outputs	With a VersaMax CPUx05 CPU: A maximum of 3584 bytes of input data and 3584 bytes of output data With a VersaMax PROFINET Network Slave: A maximum of 1440 bytes of input data and 1440 bytes of output data With either CPU or PNS head end, a maximum of 244 bytes of input data and 244 bytes of output data for each slave.	N/A
Network Data Rate	9.6 Kbaud to 12 Mbaud	9.6 Kbaud to 12 Mbaud	N/A
Network Topology	Linear bus, terminated at both ends. Stubs are possible	Linear bus, terminated at both ends. Stubs are possible.	N/A
Transmission Media	Shielded, twisted pair cable	Shielded, twisted pair cable	N/A
Connector	9-pin D-sub connector	9-pin D-sub connector	N/A
Number of Nodes	N/A	N/A	N/A
User Diagnostic Data	N/A	Slave Status Bit Array Table, Firmware Module Revision, Slave Diagnostic Address	N/A
Power Consumption	460 mA maximum from 5 V output, 5 mA from +3.3 V output	450 mA maximum from 5 V output, 5 mA from +3.3 V output	N/A
Dimensions (W x H x D)	110 mm (4.3 in) \times 66.8 mm (2.63 in) \times 50 mm (1.956 in), not including the height of the carrier or the mating connectors	110 mm (4.3in) \times 66.8 mm (2.63 in) \times 50 mm (1.956 in), not including the height of the carrier or the mating connectors	66.8 mm (2.63 in) \times 133.4 mm (5.25 in) \times 70 mm (2.75 in), not including the height of DIN-rail