

HT-20 Specification Sheet

SHEET # 940-2T074

INSTALLATION NOTES


The HT-20 is AMCI's most popular heavy duty, single turn transducer. The HT-20 is IP67 rated and will survive most industrial applications including washdowns. The HT-20 is not recommended for corrosive environments. AMCI manufactures the HT-20K and HT-20L transducers with stainless steel shafts for these applications. The HT-20C with stainless steel shaft and body is also available.

Because of the large shaft bearings used in the HT-20, gears or pulleys can be directly mounted onto the shaft. However, use a flexible coupler when attaching the transducer to a machine shaft. Even a small mis-alignment or movement in the machine shaft can cause very large radial and axial loads on the transducer bearings if the two shafts are directly coupled.

When face mounting the HT-20, the pilot hole for the shaft should be at least 1.19" in diameter so that the bearing can pass through the hole.

Because the HT-20 is an absolute sensor, it cannot "lose counts" as an incremental transducer can. If the HT-20 appears to be losing counts when operating, the usual cause is a shaft slipping in a loose coupler. Check all mechanical couplings and use shaft keys wherever possible.

DIMENSIONAL DRAWING



SPECIFICATIONS

Mechanical

Shaft Loading: Radial: 100 lbs. max.
Axial: 50 lbs. max.
Bearing life rated at 2×10^9 revolutions minimum at specified shaft load.
Starting Torque: 8 oz.in. @ 25°C
Moment of Inertia: 6.25×10^{-4} oz-in-sec² max.
Weight: 4.0 lbs

Environmental


Shock: 50 g's for 11 milliseconds
Vibration: 15 g's to 2000 Hz
Operating Temp: -40 to 125°C (-40 to 257°F)
Enclosure: Anodized Aluminum Body
1070 Carbon Steel Shaft
IP67 when mating connector properly sealed.

HT-20 Specification Sheet

CONNECTOR PINOUT

The figure below shows the connector pinout to industry standard designations and wire colors. Mating connectors available from AMCI are given in the table on the right.

Military Equivalent: MS3102E16S-1P



COMPATIBLE CABLES

Cables for the HT-20 single turn resolver transducer can be ordered from AMCI. The mating connector is preinstalled and all connections are 100% factory tested.

As shown in the table below, three different versions are available, with the difference being the installed mating connector. For all part numbers, "x" specifies the length of the cable in feet.

Cable #	AMCI Connector #	Military Equ. #
CTL-x	MS-16 (Straight)	MS3106A16S-1S
CTL-x/MS18	MS-18 (Rt. Angle)	MS3108A16S-1S
CTL-x/MS161	MS-161 (Watertight)	MS3106F16S-1S

FOR MORE INFORMATION

If you need more information on using the HT-20, use these three resources:

- * If you have internet access, check our website at <http://www.amci.com>. We've worked hard to make our site the repository of information you need to specify and use AMCI products. New product news, product specifications, compatibility tables, application notes, and PDF manuals are all available 24 hours a day.
- * You can also call AMCI for sales or technical support at (860) 585-1254 from 8AM to 5PM EST, Monday through Friday. An applications engineer will be available to assist you.
- * Finally, you can e-mail us at sales@amci.com or techsupport@amci.com.